

300 Series Pin & Barrel Type Continuous Stainless Steel Hinges

Continuous hinges shall be full height piano-type hinge providing full height door support.

- Supports weights up to 600 lbs. 4' 0" maximum door width
- Material to be 14 gauge, stainless steel
- .25 diameter stainless steel pin (except MB option)
- Exterior barrel diameter .438 (7/16)
- Each knuckle 2", including split nylon bearing at each separation for a quiet, smooth, self-lubricating operation
- Finish: US32D Satin Stainless Steel (630). Optional Finishes: US32 Bright Stainless Steel (629), or Scratch-Resistant Powder Coated Paint.
- Non-Handed
- All hinges shall be furnished with manufacturer's recommended hardware pack per specific model application
- Must be able to carry Warnock Hersey Int. or UL for fire rated doors and frames up to 3 hours
- Hinges shall meet ANSI/BHMA Standard A 156.26 Grade 1
- Symmetrically templated hole pattern

**Note: 10-Year Warranty on all Continuous Hinges
*25-Year with Medical Bearings (MB)**

Note: If HG 305 or HG 310 – 1 3/8 Adjusta-Screw fastener with 10-32 thread x hex adjustment must be supplied

Note: Fire label for doors and frames should be placed on the header and top rail of fire rated doors and frames